



# Dantex CP Primer®

Primer for concrete & worn/polished asphalt surfacing



## MATERIAL SAFETY DATA SHEET Latest Revision - June 2020

1/5

**PRODUCT:** Dantex CP Primer

**OTHER NAMES:** Dantex Maxicrete Primer

**STOCK CODES:**

### 1. SUBSTANCE / PREPARATION & COMPANY IDENTIFICATION:

**CHEMICAL NATURE:** Primer mixture

**COMPANY:** Walker Sealants Limited  
Outland Head Works  
Hope Valley, Bradwell  
Derbyshire, S33 9JP

**TEL:** +44 (0)1433 621 600

**EMAIL:** [sales@walkersealants.co.uk](mailto:sales@walkersealants.co.uk)

**WEB:** [www.walkersealants.co.uk](http://www.walkersealants.co.uk)

### 2. COMPOSITION / INFORMATION ON INGREDIENTS:

**Contains:** Mixture

### 3. HAZARD IDENTIFICATION:

**Highly Flammable Liquid and Vapour.**  
**Causes Serious Skin Irritation.**  
**May cause drowsiness or dizziness**

The product is classified as dangerous according to Directive 1999/45/EC and its amendments.



**Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.**  
**Use only outdoors or in a well ventilated area.**

### 4. FIRST AID MEASURES:

In all cases if symptoms are severe, persist or cause concern obtain immediate medical advice.

**INHALATION:** Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.

**EYES:** Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.

**SKIN:** Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.

**INGESTION:** If swallowed, seek medical advice immediately and show the container or label. Keep person warm and at rest. Do NOT induce vomiting.



### MATERIAL SAFETY DATA SHEET Latest Revision - June 2020

2/5

#### 5. FIRE FIGHTING MEASURES:

**HIGHLY FLAMMABLE LIQUID AND VAPOUR. IN A FIRE OR IF HEATED, A PRESSURE INCREASE WILL OCCUR AND THE CONTAINER MAY BURST WITH A RISK OF EXPLOSION. RUN OFF TO SEWER MAY CREATE FIRE OR EXPLOSION HAZARD.**

**SUITABLE EXTINGUISHING MEDIA:** Alcohol resistant foam, Carbon Dioxide, Dry Chemicals, Water Fog/Mist

**PROTECTIVE EQUIPMENT:** Use full protective clothing and self-contained breathing apparatus. Fires in confined spaces should be dealt with by trained personnel.

#### 6. ACCIDENTAL RELEASE MEASURES:

- No action shall be taken involving any personal risk or without suitable training.
- Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering.
- Do not touch or walk through spilt material.
- Shut off all ignition sources.
- No flares, smoking or flames in hazard area
- Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate.
- Put on appropriate personal protective equipment.
- Do not discharge into drains or rivers.

**Absorb into dry sand or earth. Transfer to closable, labelled salvage, container for disposal. Do not use equipment to clean up that may produce sparks.**

#### 7. HANDLING & STORAGE:

- Prevent the creation of flammable or explosive concentrations of vapours in air and avoid vapour concentrations higher than the occupational exposure limits.
- In addition, the product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Electrical equipment should be protected to the appropriate standard.
- Mixture may charge electrostatically: always use earthing leads when transferring from one container to another.
- Operators should wear antistatic footwear and clothing and floors should be of the conducting type.
- Keep away from heat, sparks and flame. No sparking tools should be used.
- Avoid contact with skin and eyes. Avoid the inhalation of dust, particulates, spray or mist arising

**Manufactures & Suppliers of:**  
Joint Sealants  
Bituminous Repair Compounds  
High Friction Surfacing  
Colour Coated Aggregates  
**The Complete Highway Service**

**Walker Sealants Limited**  
Manufacturing & Sales Division  
Outland Head  
Bradwell, Hope Valley  
Derbyshire, S33 9JP  
Tel: 01433 621 600



Directors: J.S. Walker, J.G.R. Walker  
Company Reg No. 4041871

**A member of the Walker Group of Companies**



### MATERIAL SAFETY DATA SHEET Latest Revision - June 2020

3/5

from the application of this mixture. Avoid inhalation of dust from sanding.

- Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed.
- Put on appropriate personal protective equipment Never use pressure to empty. Container is not a pressure vessel.
- Always keep in containers made from the same material as the original one.
- Comply with the health and safety at work laws.

#### 8. EXPOSURE CONTROL / PERSONAL PROTECTION:

Ensure there is sufficient ventilation of the area.

**SKIN PROTECTION:** Wear protective clothing.

**HAND PROTECTION:** 1 - 4 hours (breakthrough time): Butyl rubber gloves (0.60mm)

**FOOT PROTECTION:** Enclosed footwear

**EYE PROTECTION:** Wear safety glasses. Ensure eye bath is to hand.

**INHALATION:** Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use. Recommended: organic vapour (Type A) and particulate filter (EN141).

#### 9. PHYSICAL & CHEMICAL PROPERTIES:

**STATE:** Liquid **COLOUR:** Various

**ODOUR:** Not available **FORM:** Liquid

**SOLUBILITY:** Not soluble in water

#### 10. STABILITY & REACTIVITY:

**STABILITY:** Stable under recommended normal conditions and rooms temperature. Hazardous reactions will not occur under normal transport or storage conditions.

**MATERIALS TO AVOID:** Keep away from the following materials to prevent strong exothermic reactions: oxidising agents, strong alkalis, strong acids.

#### 11. TOXICOLOGICAL INFORMATION:

Repeated exposure may cause skin dryness or cracking. Irritation and redness of eyes, the eyes may water profusely. May cause drowsiness or dizziness.



### MATERIAL SAFETY DATA SHEET Latest Revision - June 2020

4/5

#### 12. TRANSPORT INFORMATION:

UN Number UN1263

Shipping Name – Paint Related Material

Transport Class 3, Packing group II

Not environmentally hazardous.



#### 13. DISPOSAL INFORMATION:

The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

Transfer to a suitable container and arrange for collection by specialised disposal company.

The user's attention is drawn to the possible existence of regional or national regulations regarding disposal. Do not allow to enter drains or watercourses.

#### 14. ECOLOGICAL INFORMATION:

- Product is Volatile
- This product has not been tested for biodegradation.
- Do not allow to enter drains or watercourses.
- The mixture has been assessed following the summation method of the CLP Regulation (EC) No 1272/2008 and is not classified as hazardous to the environment.

#### 15. REGULATORY INFORMATION:

Safety, health and environmental regulations/legislation specific for the substance or mixture EU Regulation (EC) No. 1907/2006 (REACH)

A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

#### 16. OTHER INFORMATION:

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

**Manufactures & Suppliers of:**  
Joint Sealants  
Bituminous Repair Compounds  
High Friction Surfacing  
Colour Coated Aggregates  
**The Complete Highway Service**

**Walker Sealants Limited**  
Manufacturing & Sales Division  
Outland Head  
Bradwell, Hope Valley  
Derbyshire, S33 9JP  
Tel: 01433 621 600



Directors: J.S. Walker, J.G.R. Walker  
Company Reg No. 4041871

**A member of the Walker Group of Companies**



H315 Causes skin irritation.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.

#### PRODUCT USE:

The provisions of Safety Data Sheets come under the REACH and CHIP regulations. This is in addition to the users of products supplied by Walker Sealants Limited should take appropriate measures to ensure working practices are in accordance with the Control of Substances Hazardous to Health (COSHH).

The information in the MSDS was obtained from sources believed to be reliable. The information is provided with no warranty, expressed or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the material are beyond our control and may be beyond our knowledge. For this and other reasons we assume no responsibility and expressly disclaim liability for loss, damage or expense arising from, or in any way connected with the handling, storage, use or disposal of this material.

---

This data is provided for your information and your attention is drawn to the appropriate package labelling and the product safety data sheet. Users of the product must ensure its proper use in accordance with good industrial practices, proper medical advice and any official or Government notice or publication. This information is provided gratuitously independent of any sale of the product and does not form part of any contract or sale nor does it constitute any representation, warranty or condition of merchantability or fitness for any purpose.

---