



#### **1. GENERAL DESCRIPTION:**

**Armourgrout** is a polymer modified bituminous hot melt adhesive for bonding surface mounted and inset reflective road studs on concrete and asphalt carriageways.

#### 2. PRODUCT:

The **Armourgrout** is a blend of polymer modified penetration grade bitumen and fine limestone extender conforming to the following specification. Generally termed "hot melt" type as it requires heating in order to liquify for application. **BRAND NAME:** Standard Hot Melt Adhesive BP05

#### 3. PHYSICAL PROPERTIES:

SPECIFIC GRAVITY:	1.80 ± 0.05	
PRODUCT POURING TEMPERATURE:	190 ± 10°C	
MAXIMUM SAFE HEATING TEMPERATURE:	230°C	
FLOW RESISTANCE @ 60%:	>5mm	
PENETRATION VALUE:	16 ± 2 dmm	
SOFTENING POINT:	95 ± 5°C	
FLASH POINT - COC:	> 250°C	
4. SPECIFICATION:		
POLYMER MODIFIED BINDER:	30 ± 3%	
LIMESTONE FILLER - MINIMUM 80% PASSING 75	<b>5UM SIEVE</b> : 70 ± 3%	

#### 5. CHEMICAL RESISTANCE:

Bituminous products soften in contact with petroleum solvent and mineral oils. The product has good resistance to dilute acids and alkalis.

**STORAGE:** Store in a cool dry place preferably under cover and away from direct sunlight.

**COMPOSITION:** A blend of polymer modified bitumen and fine limestone.

**PACKAGING:** Multiply silicone lined sacks - 25Kgs Net.

#### 6. SAFE HANDLING PRECAUTIONS:

- \* Do not exceed the maximum safe heating temperature.
- \* Do not allow the hot material to come into contact with water as the product WILL REACT VIOLENTLY.






\*



# ider 2021



# 7. ACUTE HEALTH HAZARDS & ADVICE:

**Armourgrout** presents no acute health hazard at ambient temperature. However, as these materials are normally handled at elevated temperatures when their physical state changes to a liquid, the bitumens present in these products give off fumes which are undesirable to inhale as very small quantities of **HYDROGEN SULPHIDE** may be present in the bitumen.

# **RECOMMENDED PROTECTIVE CLOTHING:**

Overalls, Goggles/Visor, Armlet Gloves and Closed Safety Boots **AT ALL TIMES** when handling hot product.

# INHALATION:

Inhalation of the vapours should be avoided.

# **INHALATION FIRST AID:**

Remove the affected person to fresh air. If breathing has stopped administer artificial respiration. Give cardiac massage if necessary. If the person is breathing but unconscious place in the recovery position. Obtain medical assistance immediately.

#### SKIN CONTACT:

Bituminous products present no acute health hazards to the skin other than burning when handling at elevated temperatures.

# SKIN CONTACT FIRST AID:

Flush the contaminated skin with cold water. DO NOT ATTEMPT TO REMOVE THE BITUMEN. Cover the burn with a sterile dressing. Do not apply any medication to the affected part. Obtain medical attention immediately.

# EYE CONTACT:

Contact with fumes may cause irritation and redness.

# EYE CONTACT FIRST AID:

Irrigate with copious amounts of water for 10 / 20 minutes and seek medical advice immediately.

# **PRECAUTIONS:**

Avoid contact with the skin by use of suitable protective clothing.

Manufactures & Suppliers of: Joint Sealants Bituminous Repair Compounds High Friction Surfacing Colour Coated Aggregates The Complete Highway Service Walker Sealants Limited Manufacturing & Sales Division Outland Head Bradwell, Hope Valley Derbyshire, S33 9JP Tel: 01433 621 600



Directors: J.S. Walker, J.G.R. Walker Company Reg No. 4041871 A member of the Walker Group of Companies





MATERIAL DATA SHEET Latest Revision - December 2021

#### **TRANSPORTATION:**

Not classified as dangerous for transportation.

#### FURTHER INFORMATION:

Additional information on the product is given in the system Safety Data Sheet and Installation Method Statement or by contacting Walker Sealants Ltd.

This data is provided for your information and your attention is drawn to the appropriate package labelling and the product safety data sheet. Users of the product must ensure its proper use in accordance with good industrial practices, proper medical advice and any official or Government notice or publication. This information is provided gratuitously independent of any sale of the product and does not form part of any contract or sale nor does it constitute any representation, warranty or condition of merchantability or fitness for any purpose.