



### INSTALLATION METHOD STATEMENT Latest Revision - September 2021

1/2

#### 1. GENERAL DESCRIPTION:

**CP Primer** is a primer for concrete and worn/polished asphalt surfacing. It improves the adhesion of thermoplastic road marking material to concrete, asphalt and other bituminous surfaces.

#### 2. PRODUCT:

**CP Primer** is solvent based with a low viscosity to facilitate deep penetration into substrates.

#### 3. SURFACE PREPARATION:

- 3.1 The area to which the system is to be applied shall be clearly defined by the client prior to commencement of work.
- 3.2 Clean and dry the surface to be treated. Ensure it is free from any contamination including dust, dirt, oil grease, laitance and curing agents. The surface must be stable and not prone to flaking, dusting or spalling. Make sure it is free from salt, ice and moisture. If necessary power wash the surface and dry with a hot air lance before application.

#### 4. MIXING & APPLICATION:

- 4.1 Application should only be carried out by fully trained operatives.
- 4.2 **CP Primer** must not be applied in periods of continuous or heavy rain.
- 4.3 Apply in temperatures between 5°C to 35°C.

#### 5. INSTALLATION PROCEDURE

- 5.1 Apply using a sprayer, brush or roller.
- 5.2 Totally cover the prepared surface with a thin, even coating of **CP Primer**.
- 5.3 Do not pour onto the surface, to avoid ponding brush out where necessary.
- 5.4 Ensure **CP Primer** is thoroughly dry before applying subsequent thermoplastic materials.
- 5.5 It is advisable to try a test area first before proceeding with the main application.

#### 6. SYSTEM SAFE HANDLING PRECAUTIONS:

- 6.1 **CP Primer** contains flammable solvents.
- 6.2 Keep away from sources of ignition.
- 6.3 No smoking.
- 6.4 Always wear the recommended protective clothing.



- 6.5 Always use outside in well ventilated areas.
- 6.6 Do not exceed recommended application temperatures.
- 6.7 Store in a cool dry well-ventilated place suitable for storing flammable materials.

#### 7. SAFETY CLOTHING & EQUIPMENT:

The following safety clothing and equipment must be worn **AT ALL TIMES** when handling, mixing or applying **CP Primer** materials:

<b>Hand Protection:</b>	Gloves - Industrial type, heat resistant with elasticated sleeves.
<b>Eye Protection:</b>	Safety Glasses, Goggles, Face Shield if there is a risk of splashing or when spraying.
<b>Skin Protection:</b>	High Visibility Jacket, Hard Safety Helmet, Overalls (Flame retardant), Closed Safety Boots.
<b>Respiratory Protection:</b>	Wear a vapour mask.

---

This data is provided for your information and your attention is drawn to the appropriate package labelling and the product safety data sheet. Users of the product must ensure its proper use in accordance with good industrial practices, proper medical advice and any official or Government notice or publication. This information is provided gratuitously independent of any sale of the product and does not form part of any contract or sale nor does it constitute any representation, warranty or condition of merchantability or fitness for any purpose.

---

**Manufactures & Suppliers of:**  
Joint Sealants  
Bituminous Repair Compounds  
High Friction Surfacing  
Colour Coated Aggregates  
**The Complete Highway Service**

**Walker Sealants Limited**  
Manufacturing & Sales Division  
Outland Head  
Bradwell, Hope Valley  
Derbyshire, S33 9JP  
Tel: 01433 621 600



Directors: J.S. Walker, J.G.R. Walker  
Company Reg No. 4041871

**A member of the Walker Group of Companies**